



NO AIR TANKS ON OUTSIDE OF FRAME
 NEED 264" [6706] OF CLEAR AND STRAIGHT FRAME TO MOUNT MACROPAVER
 BATTERY BOX LOCATION CAN BE IN EITHER POSITION AS SHOWN
 FUEL TANK MAY NEED TO BE MOVED IF REQUIRED TO LOCATE AS NOTED
 FRONT AXLE CAPACITY: 20,000 LB [9072 KG], REAR AXLE CAPACITY: 46,000 LB [20866 KG]
 ENGINE: 300HP MIN. REAR AXLE RATIO: 4.75:1 to 5.25:1
 SLURRY PRODUCTION SPEED RANGE REQ'D: 2.5-4.5 MPH (4.0-7.25 KPH) @ 1200-1500 RPM IN LOWEST TWO GEARS

www.slurry.com
 13024 LAKE RD., P.O. BOX 178, HICKMAN, CA 95323
 PH. (209) 874-2357 FAX (209) 874-1174

This drawing is the property of Reed International, Inc., DBA VSS Macropaver. It includes the principles of design, is the property of Reed Int. and is submitted with the agreement that it is not to be reproduced, copied, or loaned, in any part or whole. It is not to be used in any manner that may constitute a detriment directly or indirectly to Reed International. Acceptance of this drawing is an agreement to the above.

TITLE:	MACROPAVER 12D	REVISION:	A	EQUIPMENT REF:	
SIZE:	A	DRAWN BY:	MLC	DRAWING NUMBER:	MB240202.dwg
DATE:	2/5/13	SCALE:		SHEET:	1 OF 1
CABOVER CHASSIS SPEC.					