

# VSS Microsurfacing Box<sup>®</sup>

## Slurry Seal/Microsurfacing Equipment Attachments



**Advanced design and construction of the heavy-duty Microsurfacing Box allows the Macropaver<sup>®</sup>, Minimac<sup>®</sup> or other machines to apply a wide range of microsurfacing with quality and consistency.**

An inside skid plate allows the operator to adjust the box to conform to previous application passes.

### OTHER FEATURES

- Telescoping walking platform
- Heavy-duty skids (tungsten-carbide skids available)
- Hydraulically-driven spiral flight augers front & back each side
- Urethane squeegee rubber throughout
- Full, variable strike-off height adjustment right, left & center.
- Adjustable center crown control
- 7.6 cm (3 in) edge clearance laydown design
- Quick connecting side shift and drag bars
- Adjustable edge strike-off for tapered joint feathering right and left

Material is delivered in widths from 2.44 m to 4.27 m (8 ft to 14 ft) with the Macropaver box and 1.83 m to 3.05 m (6 ft to 10 ft) with the Minimac box. Box width is adjustable in 15 cm (6") increments.

A patented secondary strike-off and trailing fully adjustable texture flap system provides uniform textured slurry seal material.

### SPECIFICATIONS

	Macropaver <sup>®</sup>	Minimac <sup>®</sup>
<b>Width</b> (Shipping Dimensions)	2.58 m (102")	1.98 m (78")
<b>Length</b>	2.24 m (88")	2.24 m (88")
<b>Auger</b>	23 cm (9") Ribbon Flighting	23 cm (9") Ribbon Flighting
<b>Skids</b>	Heavy-duty, abrasion-resistant, 1.83 m (6 ft) lg.	Heavy-duty, abrasion-resistant, 1.83 m (6 ft) lg.
<b>Strike-Offs</b>	Steel & urethane rubber	Steel & urethane rubber

U.S. and International Patents Pending  
VSS reserves the right to make changes in specifications at any time as part of our continuing program of product improvement. © 2014

**THE RIGHT SOLUTIONS, RIGHT NOW**  
slurry.com



a division of Reed International