

VSS Residential Microsurfacing Box[®]

Slurry Seal/Microsurfacing Equipment Attachments



A shortened frame design of the heavy-duty Residential Microsurfacing Box allows the Macropaver[®], Minimac[®] or other machines to apply microsurfacing within more confined residential areas.

OTHER FEATURES

- Heavy-duty Hardox[™] skids
- Hydraulically-driven spiral flight augers front & back each side
- Urethane squeegee rubber throughout
- Full, variable strike-off height adjustment right, left & center.
- Adjustable center crown control
- Quick connecting side shift and drag bars

Material is delivered in a 3.81 m (12 ft 6 in) fixed width.

A secondary strike-off and trailing fully adjustable texture flap system provides uniform textured slurry seal material.

SPECIFICATIONS

Width 4.29 m (168-3/16")
(Shipping Dimensions)

Length 1.37 m (54")

Auger 23 cm (9") Ribbon Flighting

Skids Heavy-duty, abrasion-resistant, 0.76 m (2 ft 6 in) lg.

Strike-Offs Steel & urethane rubber

U.S. and International Patents Pending

VSS reserves the right to make changes in specifications at any time as part of our continuing program of product improvement. © 2017

THE RIGHT SOLUTIONS, RIGHT NOW
slurry.com



a division of Reed International